

## Delta Bond-It

### Water Based Low Viscosity Rinseable Wash

#### Description

DELTA Bond-It is clear, water based low viscosity solution.

#### Uses

A wash/rinse for aged EPDM membranes for preparing the surface for an elastomeric finish coat. May also be used as a wash/rinse for single-ply aged TPO, PVC membranes.

#### Product Application

Surface must be power washed to remove dirt, loose paint and rust, excessive chalk, and other foreign materials before application of DELTA Bond-It. Surface must be completely dry prior to application. Apply by suitable spray pump such as garden pump etc; Allow the wash solution to stand 10-15 minutes to wet and react with the EPDM surface. Rinse the excess solution out of the roof with the help of squeegee.

#### Technical Data

|                     |               |
|---------------------|---------------|
| Color               | Clear         |
| pH.                 | 13-13.5       |
| Rinse Time. Minutes | 12-15         |
| VOC. g/l            | <55           |
| Specific gravity    | 1             |
| Clean up            | MineralSpirit |

#### Rate of Application

400-500 Ft.<sup>2</sup>/Gallon

#### Precaution

Do not apply below 50°F (10°C)  
Keep product away from freezing.

#### Packaging

5 gallon Pail,

#### Product Warranty

5 to 15 years extendable limited warranty. The sole remedy for goods not in conformance with any warranty is replacement of the product or return of purchase price. The Delta Coatings & Sealants Inc. shall not be liable for any other damages included but not limited to labor expenses

