

Delta Seal

Water Based, 100% Acrylic, Paving Stone & Concrete Sealer

Description

Crafted from pure acrylic resin, Delta Seal coating significantly extends the life span of building exterior, Interlocking pavers, flagstone and concrete while maintaining its original color. It forms a durable protective layer that shields against the harsh Canadian climate. Perfect for regions with strong winds, it prevents damage from frost, rain, UV rays. Being water-based it emits no unpleasant fumes and is environmentally friendly.

Suitable For

- Concrete driveways, sidewalks, floors.
- Stamped, stenciled, colored, acid stained concrete.
- Concrete pavers and precast units.
- Cultured stone
- Terrazzo

Benifits

- Non-yellowing sealer provides protection and improved appearance to concrete.
- Low odor
- Excellent abrasion and blush resistance
- Can be applied over previous coats of sealers – water based and solvent based.
- Excellent re-coatability.

Surface Preparation

- Cover vegetation, vehicles, and adjacent surfaces that are not to be treated.
- Remove any debris and detached granules with a leaf blower.
- Apply 10% solution of Muriatic acid to the surface.
- Wait for 3 to 5 minutes.
- Apply a neutralizing solution of 1 pound baking soda in a gallon of water.
- Wait for 5 to 10 minutes,
- Rinse the surface thoroughly and let dry

Properties

Appearance: White liquid, dries clear
 Solid Content: >10-25%
 Drying Time: 2-3 hours at room temperature (50% humidity)
 V.O.C.: 52g /lit.

Available Finishes

High Gloss, Low Gloss & Natural Look

Application

- Ensure surface is clean, dry, the temperature is between 4°- 29°C and no rain is forecasted for the next 24 hours.
- Apply with roller(12 to 19 mm) or garden sprayer
- Do not dilute, shake well or stir the product before and during application.
- Apply two crossed coats of Delta Seal in succession, the second coat shall only be applied once the first coat is dry.

Coverage

Concrete / Pavers / Precast Units

1st Coat: 300 to 400 ft²/gal

2nd Coat: 300 to 400 ft²/gal

*Coverage rates are approximations. Actual coverage will vary based on temperature, texture, and substrate porosity

Storage

Keep away from freezing. Store in a cool, dry place.

Cleaning & Disposal

Wash tools and hands with warm, soapy water. Consult municipality regarding the disposal of empty containers.

Packaging & Shelf Life

Delta Seal High Gloss, 01 Gallon, 5 Gallon Bucket.
 Delta Seal Low Gloss, 01 Gallon, 5 Gallon Bucket.
 Delta Seal Natural Look, 01 Gallon, 5 Gallon Bucket.
 1 year if remains unopened and be kept away from freezing.

Product Warranty

The sole remedy for goods not in conformance with any warranty is replacement of the product or return of purchase price. The Delta Coatings & Sealants Inc. shall not be liable for any other damages included but not limited to labor expenses

