Delta Sheen

Solvent Based, Paving Stone & Concrete Sealer

Description

Crafted from 100% acrylic solvent resin, Delta Sheen coating significantly extends the life span of building exterior, Interlocking pavers, flagstone and concrete while maintaining its original color. It forms a durable protective layer that shields against the harsh Canadian climate. Perfect for regions with strong winds, it prevents damage from frost, rain and UV rays.

Compliance

ASTM C 309 Type 1, Class A or B ASTM C 1315 Type 1, Class A

Suitable For

- · Concrete driveways, sidewalks, floors.
- · Stamped, stenciled, colored, acid stained concrete.
- Concrete pavers and precast units.
- · Cultured stone
- Terrazzo

Benefits

Extending the life span of surfaces to which it is applied and maintains the original color

Surface Preparation

- Cover vegetation, vehicles, and adjacent surfaces that are not to be treated.
- Remove any debris and detached granules with a leaf blower.
- Apply 10% solution of Muriatic acid to the surface.
- Wait for 3 to 5 minutes.
- Apply a neutralizing solution of 1 pound baking soda in a gallon of water.
- Wait for 5 to 10 minutes,
- · Rinse the surface thoroughly and let dry

Properties

Appearance: Clear liquid, Solid Content: 10->25% V.O.C.: < 325 g/l

Drying Time at Room temp. &

50% Humidity: 2-4 Hours

Available Finishes

High Gloss, Low Gloss

Application

Ensure surface is clean, dry, the temperature is between 10°- 22°C and no rain is forecasted for the next 24 hours.

Apply two coats of Delta Sheen with brush or short nap solvent resistant roller(12 to 19 mm) or solvent resistant pump up sprayer

Do not dilute, shake well or stir the product before and during application.

Coverage

Upto 250 S.ft. Per gallon per coat depending upon the surface condition.

Storage

Keep away from freezing. Store in a cool, dry place.

Cleaning & Disposal

Wash tools and hands with xylene or acetone. Consult municipality regarding the disposal of empty containers.

Packaging & Shelf Life

Delta Sheen High Gloss, 01 Gallon, 5 Gallon Bucket. Delta Sheen Low Gloss, 01 Gallon, 5 Gallon Bucket. One year if remains unopened and be kept away

from freezing.

Product Warranty

5 to 15 years extendable limited warranty. The sole remedy for goods not in conformance with any warranty is replacement of the product or return of purchase price. The Delta Coatings & Sealants Inc. shall not be liable for any other damages included but not limited to labor expenses

