SAFETY DATA SHEET

DELTA SILICONE

Section 1. Identification of the hazardous chemical and of the supplier

GHS product identifier : DELTA SILICONE 66

DELTA SILICONE 66 NANO CERAMIC

DELTA SILICONE 200

Product code

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Paint or paint related material.

Uses advised against

Not applicable.

Supplier's details : Delta Coatings & Sealants Inc.

2000 Argentia Road, Suite# 400, Plaza# 3, Mississauga, ON.

L5N1V9.

Emergency telephone

number (with hours of

operation)

: US / Canada 1-647-868-3330

: SKIN SENSITIZATION - Category 1

Section 2. Hazard(s) identification

Classification according to

NCh382

Not regulated

Classification of the substance or mixture GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements: May cause an allergic skin reaction.

Precautionary statements

Prevention : Wear protective gloves. Avoid breathing vapor. Contaminated work clothing should

not be allowed out of the workplace.

Response : Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with

plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national


and international regulations.

 Date of issue/Date of revision
 : 10, Jun, 2024 Date of previous issue
 : No previous validation
 Version
 : 1
 1/11

 DELTA SILICONE 66/ DELTA SILICONE 66 Nano Ceramic/ DELTA SILICONE 200 Rubberized Silicone Coating

Section 2. Hazard(s) identification

Safety sign according to NCh1411/4



Specific classification

Specific symbol

Not applicable.Not applicable.

Hazard statements

: May cause an allergic skin reaction.

Specific hazards description

: Not available.

Other hazards which do not result in classification

: Please refer to the SDS for additional information.

Section 3. Composition/ components information

Substance/mixture : Mixture

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium Dioxide	≥10 - ≤25	13463-67-7
Methyl Tris(methylethylketoxime)silane	<10	22984-54-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Version: 1

Section 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

 Date of issue/Date of revision
 : 10, Jun, 2024 Date of previous issue
 : No previous validation
 Version
 : 1

 DELTA SILICONE 66/ DELTA SILICONE 66 Nano Ceramic/ DELTA SILICONE 200 Rubberized Silicone Coating

Section 5. Firefighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Measures to be taken in case of accidental spillage

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Additional disaster prevention measures : Evacuate danger area. Maintain proper ventilation and operate according to established emergency procedures. Do not dispose waste in drains or waterways.

Section 7. Handling and storage

Handling

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Storage

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Values indicated as "Ministry of HEALTH (Chile 4/2015): TWA / STEL" correspond LPP / LPT values under national regulation DS 594

Ingredient name	Exposure limits	
Titanium Dioxide	ACGIH TLV (United States, 7/2023). TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles	

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommended gloves: Nitrile gloves

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Version: 1

Section 8. Exposure controls/personal protection

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Nota(s): Closed shoes are recommended for protection.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator.

Version: 1

6/11

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Flash point

Physical state : Liquid. Color : Various Odor : Not available. pН : Not applicable. Melting point/freezing point : Not available. **Boiling point, initial boiling** : 100°C (212°F)

point, and boiling range

: Closed cup: 100°C (212°F) [Pensky-Martens Closed Cup]

Lower and upper explosion limit/flammability limit

: Lower: 1% Upper: 5%

Vapor pressure : 4.5 kPa (33.659 mm Hg)

Relative vapor density : Not available. **Density** : 1.39 g/cm³ Relative density : 1.39

Solubility(ies)

Media	Result
cold water	Not soluble

Solubility in water Partition coefficient: n-

octanol/water

: Not available.

: Not applicable.

Auto-ignition temperature : Not available. : Not available. **Decomposition temperature** Flow time (ISO 2431) : Not available. : Not available. **Odor threshold Evaporation rate** : Not available. **Flammability** Not available.

: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt) **Viscosity**

: Not available. **Heat of combustion**

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug I	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Methyl Tris(methylethylketoxime)silane	Category 2	-	-

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

 Date of issue/Date of revision
 : 10, Jun, 2024 Date of previous issue
 : No previous validation
 Version
 : 1
 7/11

 DELTA SILICONE 66/ DELTA SILICONE 66 Nano Ceramic/ DELTA SILICONE 200 Rubberized Silicone Coating

Section 11. Toxicological information

Inhalation : No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence/degradability

Not available.

Bioaccumulative potential

Not available.

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Chile (NCh2190.Of2003)

Not regulated.Not regulated.

Transport in bulk according

: Not regulated.

to IMO instruments

IMDG

IATA

: Not available.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

DS 43: Regulation for the Storage of Dangerous Substances.

DS 148: Sanitary Regulation on the Management of Hazardous Waste.

DS 298: Regulates the Transport of Dangerous Goods on Streets and Roads.

DS 594: Regulation on Basic Sanitary and Environmental Conditions in Workplaces.

NCh 382: Hazardous Substances Classification.

NCh 2190: Transport of Dangerous Goods; Safety Symbols.

NCh2245: Safety data sheet for chemical products – Content and order of sections.

DS N°40: Regulation on the prevention of occupational risks.

NCh1411/4: Risk prevention - Part 4: identification of hazards of materials.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

Section 15. Regulatory information

National inventory

Australia : Not determined.
Canada : Not determined.
China : Not determined.

Eurasian Economic Union: Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand : Not determined.
Philippines : Not determined.
Republic of Korea : Not determined.
Taiwan : Not determined.
Turkey : Not determined.
United States : Not determined.

The recipient should verify the possible existence of local regulations applicable to the chemical product

Section 16. Other information

History

Date of printing : 10, Jun, 2024.

Date of issue/Date of : 10, Jun, 2024

revision

Date of previous issue : No previous validation

Version : 1
Version of the Product : SHW1

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF =Bio concentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

Log Pow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

LC50 = Median lethal concentration

LD50: Median lethal dose

EC50: Half maximal effective concentration NOEC: No observed effect concentration

LPP: Weighted permissible limit LPT: Short-term permissible limit TWA: Time Weighted Average CAS: Chemical Abstracts Service

NA.: No applicable. ND.: No disposable.

Procedure used to derive the classification

Classification	Justification
SKIN SENSITIZATION - Category 1	Calculation method

References : Not available.

Indicates information that has changed from previously issued version.

Date of issue/Date of revision: 10, Jun, 2024 Date of previous issue: No previous validationVersion: 1DELTA SILICONE 66/ DELTA SILICONE 66 Nano Ceramic/ DELTA SILICONE 200 Rubberized Silicone Coating

Section 16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.